

DEKS



Dektite® Combo

Flashing over or around.
A standard Dektite and
Retrofit all in one.

- ☒ Suitable for both standard and retrofit applications
When retrofitting is requires just cut and apply clips for ease of application - Clips included in purchase
- ☒ Larger square base will cover a larger opening
So more forgiving for penetration openings and allows for steeper roof pitch
- ☒ Unique cone design
Provides 10mm (1/2") continuous contact with flashed pipe providing a watertight seal
- ☒ Clear markings in metric and imperial measurements
Makes for easier cutting to pipe size
- ☒ Size ranges - Numbers 1-10
Available in Black EPDM and Red Silicone
- ☒ Twenty year warranty
Just fit it and forget it - We've got you covered

www.deks.com.au



Combo Selection Guide

DEKS Code		Description	Pipe OD		Base		Pitch	Carton QTY
Black EPDM	Red Silicone		mm	inch	mm	inch		
DC101BC	DC201REC	Dektite Combo #1	5 - 60	¼ - 2½"	139 x 139	5½ x 5½"	0-40° or 10/12	15
DC102BC	DC202REC	Dektite Combo #2	45 - 85	1¾ - 3¼"	178 x 178	7 x 7"	0-40° or 10/12	15
DC103BC	DC203REC	Dektite Combo #3	5 - 127	¼ - 5"	221 x 221	8¾ x 8¾"	0-40° or 10/12	15
DC104BC	DC204REC	Dektite Combo #4	75 - 175	3 - 7"	285 x 285	11¼ x 11¼"	0-40° or 10/12	10
DC105BC	DC205REC	Dektite Combo #5	108 - 190	4¼ - 7½"	366 x 366	14¼ x 14¼"	0-40° or 10/12	10
DC106BC	DC206REC	Dektite Combo #6	125 - 230	5 - 9"	366 x 366	14¼ x 14¼"	0-40° or 10/12	10
DC107BC	DC207REC	Dektite Combo #7	150 - 280	6 - 11"	454 x 454	17¾ x 17¾"	0-40° or 10/12	10
DC108BC	DC208REC	Dektite Combo #8	175 - 330	7 - 13"	454 x 454	17¾ x 17¾"	0-40° or 10/12	5
DC109BC	DC209REC	Dektite Combo #9	240 - 508	9½ - 20"	705 x 705	27¾ x 27¾"	0-40° or 10/12	5
DC110BC	DC210REC	Dektite Combo #10	350 - 760	13¾ - 30"	965 x 965	38 x 36¾"	0-40° or 10/12	1
DC Clips		Combo Clips Twin						25

Available in Black EPDM or Red Silicone

EPDM will withstand constant temperatures at the roofline of -50°C (-58°F) to 115°C (239°F) and up to 150°C (302°F) intermittently

Red Silicone will withstand constant temperatures at the roofline of -50°C (-58°F) to 200°C (392°F) and up to 250°C (482°F) intermittently

Please Note That the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.

Combo Square Selection Guide

DEKS Code	Description	Square Pipe		Base		Pitch	Carton QTY
Black EPDM		mm	inch	mm	inch		
DCS103B	Dektite Combo Square	20 - 125	¾ - 5"	221 x 221	8¾ x 8¾"	0-40° or 10/12	5


Installation Instructions

Standard Application

1. Trim the cone to suit pipe size using tin snips
2. Slide down pipe using water as a lubricant
3. Apply sealant on underside of flexible aluminium base
4. Press base to the roof profile by hand. Smooth out any awkward creases. Don't fully extend to allow for vibration
5. Fasten using self sealing fasteners or pop (sealed) rivets

Retrofit Application

1. Trim cone to suit pipe size then cut seam and aluminium base using tin snips
2. With seam in downstream position wrap cone around pipe and engage 1st double clip at top of seam using multigrips
3. Engage remaining clips working down from top of cone to base
4. Apply sealant to outside of seam closure and to underside of Dektite Combo and shape to roof by hand
5. Fasten flashing down by placing a fastener either side of seam first then secure rest of base
6. Apply sealant to top of base closure and other potential leak areas



- Always use the neutral cure low modulus silicone for sealing
- In corrosive and coastal environments fix using blind aluminium rivets
- Clips Included

Need to flash a tiled roof? Contact DEKS to discuss the tile roof flashing range.